

Package: imputeMissings (via r-universe)

August 31, 2024

Type Package

Title Impute Missing Values in a Predictive Context

Version 0.0.4

Date 2024-08-24

Imports randomForest,stats

Description Compute missing values on a training data set and impute them on a new data set. Current available options are median/mode and random forest.

License GPL (>= 2)

RoxygenNote 5.0.1

NeedsCompilation no

Date/Publication 2024-08-30 10:40:08 UTC

Author Matthijs Meire [aut], Michel Ballings [aut, cre], Dirk Van den Poel [aut]

Maintainer Michel Ballings <michel.ballings@gmail.com>

Repository <https://ballings.r-universe.dev>

RemoteUrl <https://github.com/cran/imputeMissings>

RemoteRef HEAD

RemoteSha 864f1aa5e332e388702c6f1fd2fd78539863fbb5

Contents

compute	2
impute	3

Index	6
--------------	----------

 compute

Compute the missing values to later impute them in another dataset

Description

When the median/mode method is used: character vectors and factors are imputed with the mode. Numeric and integer vectors are imputed with the median. When the random forest method is used predictors are first imputed with the median/mode and each variable is then predicted and imputed with that value. For predictive contexts there is a `compute` and an `impute` function. The former is used on a training set to learn the values (or random forest models) to impute (used to predict). The latter is used on both the training and new data to impute the values (or deploy the models) learned by the `compute` function.

Usage

```
compute(data, method = "median/mode", ...)
```

Arguments

<code>data</code>	A data frame with dummies or numeric variables. When <code>method=="median/mode"</code> columns can be of type "character". When <code>method="randomForest"</code> columns cannot be of type "character".
<code>method</code>	Either "median/mode" or "randomForest"
<code>...</code>	additional arguments for <code>randomForest</code>

Value

Values or models used for imputation

Author(s)

Matthijs Meire, Michel Ballings, Dirk Van den Poel, Maintainer: <Matthijs.Meire@UGent.be>

See Also

[impute](#)

Examples

```
#Compute the values on a training dataset and impute them on new data.
#This is very convenient in predictive contexts. For example:

#define training data
(train <- data.frame(v_int=as.integer(c(3,3,2,5,1,2,4,6)),
  v_num=as.numeric(c(4.1,NA,12.2,11,3.4,1.6,3.3,5.5)),
  v_fact=as.factor(c('one', 'two',NA, 'two', 'two', 'one', 'two', 'two')),
  stringsAsFactors = FALSE))
```

```

#Compute values on train data
#randomForest method
values <- compute(train, method="randomForest")
#median/mode method
values2 <- compute(train)

#define new data
(newdata <- data.frame(v_int=as.integer(c(1,1,2,NA)),
                      v_num=as.numeric(c(1.1,NA,2.2,NA)),
                      v_fact=as.factor(c('one', 'one', 'one', NA)),
                      stringsAsFactors = FALSE))

#locate the NA's
is.na(newdata)
#how many missings per variable?
colSums(is.na(newdata))

#Impute on newdata
impute(newdata,object=values) #using randomForest values
impute(newdata,object=values2) #using median/mode values

#One can also impute directly in newdata without the compute step
impute(newdata)

#Flag parameter
impute(newdata,flag=TRUE)

```

impute

Impute missing values with the median/mode or randomForest

Description

When the median/mode method is used: character vectors and factors are imputed with the mode. Numeric and integer vectors are imputed with the median. When the random forest method is used predictors are first imputed with the median/mode and each variable is then predicted and imputed with that value. For predictive contexts there is a `compute` and an `impute` function. The former is used on a training set to learn the values (or random forest models) to impute (used to predict). The latter is used on both the training and new data to impute the values (or deploy the models) learned by the `compute` function.

Usage

```
impute(data, object = NULL, method = "median/mode", flag = FALSE)
```

Arguments

<code>data</code>	A data frame with dummies or numeric variables. When <code>method=="median/mode"</code> columns can be of type "character". When <code>method="randomForest"</code> columns cannot be of type "character".
-------------------	--

object	If NULL impute will call compute on the current dataset. Otherwise it will accept the output of a call to compute
method	Either "median/mode" or "randomForest". Only works if object = NULL
flag	Add dummy variables to indicate which rows have been imputed for each variable

Value

An imputed data frame.

Author(s)

Matthijs Meire, Michel Ballings, Dirk Van den Poel, Maintainer: <Matthijs.Meire@UGent.be>

See Also

[compute](#)

Examples

```
#Compute the values on a training dataset and impute them on new data.
#This is very convenient in predictive contexts. For example:

#define training data
(train <- data.frame(v_int=as.integer(c(3,3,2,5,1,2,4,6)),
                    v_num=as.numeric(c(4.1,NA,12.2,11,3.4,1.6,3.3,5.5)),
                    v_fact=as.factor(c('one', 'two', NA, 'two', 'two', 'one', 'two', 'two')),
                    stringsAsFactors = FALSE))

#Compute values on train data
#randomForest method
values <- compute(train, method="randomForest")
#median/mode method
values2 <- compute(train)

#define new data
(newdata <- data.frame(v_int=as.integer(c(1,1,2,NA)),
                    v_num=as.numeric(c(1.1,NA,2.2,NA)),
                    v_fact=as.factor(c('one', 'one', 'one', NA)),
                    stringsAsFactors = FALSE))

#locate the NA's
is.na(newdata)
#how many missings per variable?
colSums(is.na(newdata))

#Impute on newdata
impute(newdata,object=values) #using randomForest values
impute(newdata,object=values2) #using median/mode values

#One can also impute directly in newdata without the compute step
```

```
impute(newdata)  
  
#Flag parameter  
impute(newdata, flag=TRUE)
```

Index

compute, [2](#), [4](#)

impute, [2](#), [3](#)